

# 1-1/2" X 13/32" MIDGET FUSES



Amp-trap ATQ midget time-delay fuses are rated a full 500 volts AC with 42 ampere ratings from 1/10 to 30A. They are an excellent choice for supplemental protection of circuits up to 30A where the available short circuit current does not exceed 10,000A. (Not for Branch Circuit Protection).

**Features/Benefits**

- **Numerous ratings** for a wide variety of applications up to 500VAC
- **Time Delay** (12 seconds at 200% rating) for circuits with high inrush current
- Can be used with **ULTRASAFE™** Fuseholders

**HIGHLIGHTS:**

- Time Delay

**APPLICATIONS:**

- Supplemental protection of lighting, solenoid, motor, and transformer circuits

**Ratings**

- **AC:** 1/10 to 30A  
500VAC, 10kA I.R.

**Approvals**


- UL Listed to Standard 248-14
- CSA Certified to Standard C22.2 No. 248.14



**Standard Fuse Ampere Ratings, Catalog Numbers**

AMPERE RATING	CATALOG NUMBER	AMPERE RATING	CATALOG NUMBER	AMPERE RATING	CATALOG NUMBER	AMPERE RATING	CATALOG NUMBER	AMPERE RATING	CATALOG NUMBER	AMPERE RATING	CATALOG NUMBER	AMPERE RATING	CATALOG NUMBER
1/10	ATQ1/10	3/10	ATQ3/10	1-1/8	ATQ1-1/8	2	ATQ2	3-2/10	ATQ3-2/10	6	ATQ6	12	ATQ12
1/8	ATQ1/8	4/10	ATQ4/10	1-1/4	ATQ1-1/4	2-1/8	ATQ2-1/8	3-1/2	ATQ3-1/2	6-1/4	ATQ6-1/4	14	ATQ14
15/100	ATQ15/100	1/2	ATQ1/2	1-4/10	ATQ1-4/10	2-1/4	ATQ2-1/4	4	ATQ4	7	ATQ7	15	ATQ15
3/16	ATQ3/16	6/10	ATQ6/10	1-1/2	ATQ1-1/2	2-1/2	ATQ2-1/2	4-1/2	ATQ4-1/2	8	ATQ8	20	ATQ20
2/10	ATQ2/10	8/10	ATQ8/10	1-6/10	ATQ1-6/10	2-8/10	ATQ2-8/10	5	ATQ5	9	ATQ9	25	ATQ25
1/4	ATQ1/4	1	ATQ1	1-8/10	ATQ1-8/10	3	ATQ3	5-6/10	ATQ5-6/10	10	ATQ10	30	ATQ30

**Melting Time — Current Data 1/10 - 3-1/2 Amperes, 500 Volts AC**



**Melting Time — Current Data 4 - 30 Amperes, 500 Volts AC**

