



## ECF

### Quick Acting High Breaking Capacity

- 5Ø x 20 mm (0.197 x 0.787 inch)
  - Ampere Rating: 63mA to 25 A
  - Voltage Rating: 250V
  - Standards: IEC Standards
  - Option: Available Add Axial Leads
- Model No. ECF-A

#### • Electrical Characteristics:

Rated Current	1.5 In		2.1 In		2.75 In		4 In		10 In	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
63mA - 100mA	60 min	30 min	10 ms	2 sec	3 ms	300 ms	20 ms			
125mA - 25A	60 min	30 min	10 ms	3 sec	3 ms	300 ms	20 ms			



## ECT

### Time-Lag High Breaking Capacity

- 5Øx20 mm (0.197x0.787 inch)
  - Ampere Rating: 63mA to 25 A
  - Voltage Rating: 250V
  - Standards: IEC Standards
  - Option: Available Add Axial Leads
- Model No. ECT-A

#### • Electrical Characteristics:

Rated Current	1.5 In		2.1 In		2.75 In		4 In		10 In	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
63mA - 3.15A	60 min	30 min	200 ms	10 sec	40 ms	3 sec	10 ms	300 ms		
4A - 25A	60 min	30 min	600 ms	10 sec	150 ms	3 sec	20 ms	300 ms		



## UNF

### Quick Acting Low Breaking Capacity

- 6.3Ø x 32 mm ( 1/4 x 1-1/4 inch)
  - Ampere Rating: 50mA to 25 A
  - Voltage Rating: 250V
  - Standards: IEC Standards
  - Option: Available Add Axial Leads
- Model No. UNF-A

#### • Electrical Characteristics:

Rated Current	1.5 In		2.1 In		2.75 In		4 In		10 In	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
63mA - 100mA	60 min	20 min	2 ms	200 sec	1 ms	30 ms	5 ms			
125mA - 25A	60 min	20 min	20 ms	1.5 sec	8 ms	400 ms	80 ms			



## UNT

### Time-Lag Low Breaking Capacity

- 6.3Ø x 32 mm (1/4 x 1-1/4 inch)
  - Ampere Rating: 50mA to 25 A
  - Voltage Rating: 250V
  - Standards: IEC Standards
  - Option: Available Add Axial Leads
- Model No. UNT-A

#### • Electrical Characteristics:

Rated Current	1.15 In		2.1 In		2.75 In		4 In		10 In	
	Min	Min	Max	Min	Max	Min	Max	Min	Max	
50mA-2A	60 min	800 ms	20 sec	150 ms	3 sec	60 ms	1 sec	10 ms	200 ms	
2.5A-25A	60 min	800 ms	30 sec	200 ms	6 sec	80 ms	2 sec	15 ms	300 ms	



## UCF

### Quick Acting High Breaking Capacity

- 6.3Øx32 mm (1/4x1-1/4 inch)
  - Ampere Rating: 100mA to 35 A
  - Voltage Rating: 500V
  - Standards: IEC Standards
  - Option: Available Add Axial Leads
- Model No. UCF-A

#### • Electrical Characteristics:

Rated Current	1.5 In		2.1 In		4 In		10 In	
	Min	Max	Min	Max	Min	Max	Min	Max
100mA - 35A	60 min	30 min	300ms	20ms				



## UCT

### Time-Lag High Breaking Capacity

- 6.3Øx32 mm (1/4x1-1/4 inch)
  - Ampere Rating: 100mA to 25 A
  - Voltage Rating: 500V
  - Standards: IEC Standards
  - Option: Available Add Axial Leads
- Model No. UCT-A

#### • Electrical Characteristics:

Rated Current	1.5 In		2.1 In		2.75 In		4 In		10 In	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
50mA - 25A	60 min	30 min	600 ms	10 sec	200 ms	4 sec	50 ms	450 ms		